

Technical Specifications

SA 250



Type:	2 Cylinder 4 Stroke
Coolant system:	Water
Stroke:	47 mm
Bore:	58 mm
Compression ratio:	11,2:1
Angular ignition spacing:	180° / 540°
Valve controlling:	1 OHC
	2 Valve per cylinder, bucket tappets, belt drive
Lubrication:	Dry sump with external oil tank
Carburator:	2 X Dell`Orto 22 mm
Fuel:	Unleaded 95 Roz
Clutch:	Centrifugal force
Starter:	Electric
Power output:	28 PS (20 KW) bei 9500 1/min
Torque:	25 NM bei 7000 1/min
Max revolutions:	13000 1/min

Team Biland Kart-Power AG

Tel.+41 (0) 34 420 / 62 90
Fax+41 (0) 34 420 / 62 91

Buchmattstrasse 19
CH-3400 Burgdorf / Switzerland
Email : info@kart-power.com
Internet: www.kart-power.com

World – Logistik – Center

Eberhard Hoeckle GmbH
Spare Parts:
Tel.+49 (0) 7473 / 373 164
Fax+49 (0) 7473 /4014
R&D:
Tel.+49 (0) 7473 / 373 158
Fax+49 (0) 7473 / 373 / 172
Central Office:
Tel.+49 (0) 7473 / 373-0
Fax+49 (0) 7473 / 22661

Karl Jaggy Str.44
D 72116 Mössingen / Germany

E-Mail: wagner@hoeckle.de

E-Mail: biland-technik@hoeckle.de

E-Mail: info@hoeckle.de
Internet: www.hoeckle.de

V01-2004



www.kart-power.com



hoeckle
World-Logistic-Center
Team Biland Kart-Power AG

